

FloorCem SLU

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: FloorCem SLU

Product Use: Self Leveling Underlayment. Floor Seal Technology, Inc. Manufacturer/Supplier:

> 1005 Ames Ave. Milpitas, CA 95035

Phone Number: (408) 436-8181

Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)

INTERNATIONAL + 1-352-323-3500

Date of Preparation: October 12, 2013 Revision Date: October 12, 2013

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Lithium carbonate

WARNING

IRRITATING TO EYES. IRRITATING TO SKIN.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: Irritating to eyes. May cause burns in the presence of moisture. Skin: Irritating to skin. May cause burns in the presence of moisture.

May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Ingestion:

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: May cause serious chemical burns. Severe irritation, redness and pain. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Ingredient CAS# Wt. % 40 - 70 Silica, crystalline, quartz 14808-60-7 Calcium carbonate 1317-65-3 10 - 30 7 - 13 Cement, alumina, chemicals 65997-16-2 Kaolin 0.1 - 1 1332-58-7 Portland cement 65997-15-1 3 - 7

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

October 12, 2013 1/7

554-13-2

0.1 - 1



FloorCem SLU

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. If easy to do, remove contact lenses, if worn. Get medical attention

immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Call a physician if

irritation develops and persists.

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, seek medical attention or call poison control.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker

gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed and dry. Store in a cool place.

FloorCem SLU

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

Ingredient OSHA-PEL ACGIH-TLV

 $((10 \text{ mg/m}^3)/(\% \text{SiO}_2+2) \text{ TWA (resp)});$ $((30 \text{ mg/m}^3)/(\% \text{SiO}_2+2) \text{ TWA (total)});$

Silica, crystalline, quartz ((250)/(%SiO₂+2) TWA (total)), ((250)/(%SiO₂+5) mppcf TWA (resp)) Twa (total); 5 mg/m³ (total); 5 mg/m³ (resp)

Cement, alumina, chemicals
Kaolin

Not available.

15 mg/m³

10 mg/m³
Not available.
2 mg/m³
1 mg/m³ (no asbestos and

0.025 mg/m³

Portland cement 15 mg/m³ (total); 5 mg/m³ (resp) <1% crystalline silica, respirable fraction)
Lithium carbonate Not available. Not available.

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Powder.Color:Not available.Odor:Not available.Odor Threshold:Not available.

Physical State: Solid. pH: 10-12

Viscosity: Not available. **Freezing Point:** Not available. **Boiling Point:** Not available. Flash Point: Not available. Not available. **Evaporation Rate: Lower Flammability Limit:** Not available. **Upper Flammability Limit:** Not available. **Vapor Pressure:** Not available. Vapor Density: Not available.

Specific Gravity: 2.5



FloorCem SLU

Solubility in Water: Partial.

Coefficient of Water/Oil Distribution: Not available. **Auto-ignition Temperature:** Not available. Percent Volatile, wt. %: Not available.

VOC content, wt. %: 0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Acids. Ammonium Salts.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon. Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Silica, crystalline, quartz	120 g/kg, rat (TD _{lo})	Not available.
Calcium carbonate	6450 mg/kg, rat	Not available.
Cement, alumina, chemicals	Not available.	Not available.
Kaolin	Not available.	Not available.
Portland cement	Not available.	Not available.
Lithium carbonate	525 mg/kg, rat	> 2.17 mg/L 4hr, rat

Eve: Irritating to eyes. May cause burns in the presence of moisture. May cause

serious chemical burns. Severe irritation, redness and pain.

Skin: Irritating to skin. May cause burns in the presence of moisture. Symptoms may

include redness, edema, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Hazardous by WHMIS/OSHA criteria. Carcinogenicity: Hazardous by WHMIS/OSHA criteria.

Ingredient

Silica, crystalline, quartz Calcium carbonate

Lithium carbonate

Cement, alumina, chemicals Kaolin Portland cement

* See Section 15 for more information.

Chemical Listed as Carcinogen or Potential Carcinogen * G-A2, I-1, N-1, CP65

Not listed. Not listed. Not listed. G-A4 CP65



FloorCem SLU

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria. **Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Ground Classification

Not regulated

TDG Ground Classification

Not regulated

IATA Classification

Not regulated

IMDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Cement, alumina, chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Kaolin	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Lithium carbonate	Not listed.	Not listed.	Not listed.	313



FloorCem SLU

State Regulations

New Jersey Right-To-Know: Silica, Quartz; Calcium carbonate; Silicate, portland cement; Lithium carbonate. **Pennsylvania Right-To-Know:** Quartz; Limestone; Cement, portland, chemicals; Aluminum oxide. **Massachusetts Right-To-Know:** Quartz; Calcium carbonate; Portland cement.

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer. (Silica, crystalline; Titanium dioxide; Acetaldehyde; Vinyl chloride)

This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. (Lithium carbonate; Methanol)

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Cement, alumina, chemicals	DSL	Yes.
Kaolin	DSL	Yes.
Portland cement	DSL	Yes.
Lithium carbonate	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

HMIS - Hazardous Materials Identification System

Health - 2* Flammability - 0 Physical Hazard - 0 PPE – B

NFPA - National Fire Protection Association:

Health - 2 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class D2A - Carcinogenicity Class D2A - Chronic Toxic Effects Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA(O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.



FloorCem SLU

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: October 12, 2015

Version #: 1.0

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

October 12, 2013 7/7